

FREEMOTION

# LIVEAXIS™

**LOW PULL**

MODEL # F702



## CABLE STRENGTH LIVEAXIS™

The Freemotion LiveAxis™ Low Pull increases strength with live-sliding pulleys that follow a natural path of movement—giving progressive resistance and optimum muscle activation throughout the entire workout. Independent arm movements allow for specific exercises that target muscles in the back, shoulders and arms.



## LIVEAXIS™ LOW PULL

### PRODUCT FEATURES

- ① **DUAL INDEPENDENT TRACKS**  
Each pulley glides up and down on an independent track—ensuring never-ending resistance and a more effective workout.
- ② **ENCLOSED WEIGHT STACK**  
The protected, enclosed weight stack limits access to moving parts to better prevent accidents or injury.
- ③ **DESIGNED TO BE TOUGH**  
Live-sliding pulley technology allows muscles to stay at optimum activation with never-ending resistance throughout the entire movement.
- ④ **CREATE BALANCE**  
Because the pulleys on this machine swivel, specific muscles can be targeted to increase the body's stabilization and balance.
- ⑤ **INDUSTRIAL CONSTRUCTION**  
Built strong with 11 and 7-gauge steel tubing, this machine has been electrostatically powder-coated with paint tested by 2,000 hours of salt spray testing.
- ⑥ **CABLE TRAVEL**  
Extensive cable travel creates exercise flexion, single arm: 58 in (147 cm), two arms: 42 in (107 cm).
- ⑦ **KICK PLATES**  
Strong 18-gauge, stainless steel kick plates protect this machine from wear and tear.

### SPECIFICATIONS

<b>Weight Stack</b>	200 lbs (90 kg)
<b>Resistance System</b>	1 Arm- 50 lbs (22.6 kg) 2 Arms- 100 lbs (45.3 kg)
<b>Frame and Finish</b>	Powdercoated steel frame
<b>Weight Stack Configuration</b>	10 - 200 X 10 lbs (4 - 90 X 4 kg)
<b>Cable Travel</b>	2 Arm: 42 in (107 cm) 1 Arm: 58 in (147.3 cm)
<b>ADA Compliant</b>	Yes
<b>Standard Frame Colors</b>	Platinum Sparkle
<b>Product Dimensions (LxWxH)</b>	44 x 63 x 74 in (111.6 x 160 x 187.9 cm)
<b>Shipping Dimensions (LxWxH)</b>	57.2 x 39.1 x 72.8 in (145.2 x 99.3 x 184.9 cm)
<b>Shipping Weight</b>	416 lbs (188.6 kg)
<b>Regulatory Approval</b>	EN957, CE

#### WARRANTY | US AND INTERNATIONAL

10-Year Frame | 3-Year Bearings, Guide Rods, Pulleys and Weight Stacks | 1-Year Cable and Labor  
120-Days Upholstery, Handles and Accessories