MATRIX



T3xm Treadmill

Low 19 cm / 7.5 in step-on height offers easy accessibility

- Intuitive LED console displays only the feedback essential to therapists and clinicians
- WiFi connectivity accommodates optional Matrix Asset Management system
- Extended handrails with neutral-position, angled grips ensure secure entry and exit
- Extra-wide deck offers an added sense of security and freedom
- Low 0.16 km/h / 0.1 mph start speed in forward and reverse lets users with limited abilities take part in functional movement exercises
- Matrix 4.2 HP AC Dynamic Response Drive System fine-tunes response based on footfall patterns for a smooth, consistent, natural workout
- Maximum reverse speed of 6.4 kph / 4 mph
- Integrated IR sensor stops belt motion when triggered by an object or person
- Ultimate Deck System for superior performance and durability

CONSOLE	
WIFI ENABLED	Optional
DISPLAY FEEDBACK	Time of Day, Time Elapsed, Time Remaining, Distance (Kilometers or Miles), Calories, Calories per Hour, Speed, Incline, Pace, Average Pace, Heart Rate, METs, Watts, Workout Profile, Forward/Reverse
PRO:IDIOM COMPATIBLE	No
BLUETOOTH ENABLED	No
IPTV COMPATIBLE	No
WORKOUTS	Manual, Rolling Hills, Fat Burn, 5k, 10k, Target HR, Gerkin Protocol, Army PFT, Navy PRT, Marine PFT, Air Force PRT, Physical Efficiency Battery (PEB), WFI Protocol
DISPLAY TYPE	Dot-matrix LED with profile display
USB PORT	Yes
RFID COMPATIBLE	No

DRIVE SYSTEM	
DRIVE SYSTEM	Matrix 4.2 hp AC Dynamic Response Drive System™

FEATURES	
TREAD SENSE	Yes. Engages above 0.8 kph / 0.5 mph
CROSSBAR CONTROLS	No
BELT TYPE	Habasit, 2-ply commercial grade
CONTACT & TELEMETRIC HR	Yes
RUNNING AREA	152 x 51 cm / 60" x 20"
CUSHION SYSTEM	Ultimate Deck™ cushioning system
STEP-ON HEIGHT	19 cm / 7.5"
DECK TYPE	Ultimate hard-wax reversible 1" deck
INCLINE RANGE	0-15% (590-kg / 1,300-lb. thrust elevation motor)
SPEED RANGE	0.16 - 19.3 km/h / 0.1 - 12 mph forward / 0.16 - 6.4 km/h 0.1 - 4 mph reverse

TECH SPECS	
ASSEMBLED DIMENSIONS	215 x 85 x 142 cm / 84.6" x 33.5" x 56"
POWER REQUIREMENTS	20-amp dedicated circuit required, non-looped grounded
ELECTRICAL RECEPTACLE & PLUG	NEMA 5-20R 120v
SHIPPING WEIGHT	186 kg / 409 lbs.
MAX USER WEIGHT	182 kg / 400 lbs.
ASSEMBLED WEIGHT	172 kg / 378 lbs.